

The above light is designed for use on power driven vessels under 12 meters (39.4 ft.) in length operating on a nominal 12 volt or 24 volt system. In order to comply with '72 COLREGS and the U.S. Inland Rules, the following must be adhered to:

MOUNTING INFORMATION

Read all instructions before proceeding.

1. For proper light selection, positioning and configuration, refer to A.B.Y.C. Standard A-16*, the '72 COLREGS*', and the U.S. Inland Rules*. This light is usually supplied complete with 12 volt bulb (Cat. No. 0071DP0CLR), however, 24 volt bulbs (Cat. No. 0072DP1CLR) are available for 24 volt systems.
2. This light is designed to be mounted on a horizontal surface.
3. Draw an 8 inch long reference line through the center of the selected mounting location and parallel to the centerline of the boat.
4. Cut out the mounting template below. Place it on the mounting surface such that the reference line (drawn above) is directly underneath the reference line marked on the template.
5. Drill 3 holes through the template to accommodate #8 oval head mounting screws. Drill one 3/8 inch hole to accommodate the electric wiring.
6. Attach supply connections to the light, making sure to wire in accordance with both A.B.Y.C. Standard E-9* and U.S. Coast Guard Safety Standards for Boat Electrical Systems (33 CFR 183)*.
7. Mount the light in accordance with the template.
8. For final accuracy of mounting, make sure the reference line drawn in #3 above emerges from underneath the light at the exact centers of both the front and rear points of the light.

The above referenced standards can be obtained from:

(1) . American Boat & Yacht Council, Inc.
613 Third Street, Suite 10
Annapolis, MD 21403

(2). U.S. Coast Guard
Washington, D.C. 20593
(or your local C.G. office)

11/06
1218INS1

PERKO, INC.
16490 N.W. 13th Avenue
Miami, FL 33169-5707
www.perko.com

