



PERKO®

HORIZONTAL MOUNT NAVIGATION LIGHT SETS

Horizontal Mount

Fig. 0627 L.E.D. Bi-Color Light

Fig. 0227 Bi-Color Light

Certified For Use on Power Driven Vessels Under 20 Meters (65.6 ft.) in Length

White All-Round Light Options

See Pages: R-35 & R-53 See Pages: R-36 & R-55

NEW PRODUCT

CONSTRUCTION Fig 0627:

- Chrome Plated Zinc Alloy Top with Black Polymer Base or White PERKO•KOTE Zinc Alloy Top with White Polymer Base

- Red and Green L.E.D.'s

L.E.D. Version Features

- Uses 10% of the Energy Draw of Standard Lights
- Low Heat & Long Life
- L.E.D.'s have no user serviceable parts



Fig. 0627

CONSTRUCTION Fig 0227:

- Chrome Plated Zinc Alloy Top with Black Polymer Base or White PERKO•KOTE Zinc Alloy Top with White Polymer Base

- Red and Green Lenses

- 12 Volt Bulbs Included



Fig. 0227

White

Chrome

Ordering Info

Finish	Dealer Pkg.	OEM	Pkg. Qty.	Ship Wt.
	1 per Card	Bulk Pkg.	DP/OEM Bulk	Carton Lbs. DP/OEM Bulk
Chrome	0627DP0CHR	0627000CHR	1/10	0.4/3.0
White	0627DP0WHT	0627000WHT	1/10	0.4/3.0
Chrome	0227DP0CHR	0227000CHR	5/50	2.0/15.1
White	0227DP0WHT	0227000WHT	5/50	2.0/15.1

Tech Info

- Fig 0627: 12 Volt LED
- Fig. 0227: 12V Bulb Included
- Vertical Ht.: 5/8"
- Length: 3-1/2"
- Width: 2-1/4"
- Screw Size: #8

FIG 0227 SPARE PARTS ORDERING INFORMATION

Bulbs (2 per card): 0071DP0CLR. Lens (Red/Green): 0227DP0LNS.
 Black Base with Socket Assembly: 022700099A. White Base with Socket Assembly: 0227W0099A.



Fig. 0227

Note: One mile visibility light available for 0° to 20° declination mounting surfaces: 0225000CHR

NOTE: Fig. 0227 series lights meet the USCG requirements for 12-volt applications. All the above can also be used as 24-volt A.B.Y.C. A-16 certified lights on boats built prior to 11/1/03. To use as 24-volt lights while maintaining A-16 certification, replace the bulbs provided with Cat. No. 0072DP1CLR 24-volt bulbs. Contact us for 24-volt applications on new construction.