



## Horizontal Mount Bi-Color Lights

**LED 2-mile (USCG 2nm) Certified** - Patent #D665,113S  
*Use on Power Driven Vessels Under 20m (65.6 ft.) in Length*

Material: Stainless Steel  
Finish: Polished, Black, or White Powder Coated  
Dimensions: Length: 2-1/2", Width: 2-5/8", Height: 5/8"  
Screw Size: #8  
Voltage: 12V LED  
Wattage: 3.75 watts  
Amperage: <0.25 amps  
Features: Ultra Low Profile, Low Heat, Long Life



**STEALTH II** Series  
Fig. 0615 Stainless

Finish	Retail Pkg.	OEM Bulk Pkg.
Polished SS	0615DP2STS	0615000STS
Black	0615DP2BLK	0615000BLK
White	0615DP2WHT	0615000WHT

Spare gasket kit required for mounting on metallic surfaces (optional for fiberglass surfaces and included in DP package): 0615000GKT



2  
Navigation Lights

**2-mile (USCG 2nm) Certified**  
*Use on Power Driven Vessels Under 20m (65.6 ft.) in Length*

Material: Bronze Top, Polymer Base  
Finish: Chrome, Black, or White  
Dimensions: Length: 3-1/2", Width: 2-1/4", Height: 1-5/8"  
Screw Size: #8  
Contacts: Gold Plated  
Voltage: 12V (Bulb Included)  
Wattage: 10 watts  
Amperage: .80 amps



Fig. 0252 Chrome

Finish	Retail Pkg.	OEM Bulk Pkg.
Chrome	0252MB0DP1	0252MB012V
Black	0252BB0DP1	0252BB012V
White	0252WB0DP1	0252WB012V



Note: Fig. 0252 can also be used as 24-volt A.B.Y.C. A-16 certified lights on boats built prior to 11/1/03. Replace the bulbs provided with Cat. No. 0072DP1CLR 24-volt bulbs. Contact us for 24-volt applications on new construction.

**Fig. 0252:**  
Bulbs: 0071DP0CLR.  
Lens: 0247DP0LNS.  
Black Base with Socket Assembly: 0114000BLK.  
White Base with Socket Assembly: 0114000WHT.

### Spare Parts Information



L.E.D.'s have no user serviceable parts