# **PERKO**®



## **Fuel Tank Vents**

#### **Tank Vent**

Material: Bronze
Finish: Chrome Plated
For Vent Hose: 5/8" or 3/4"

Max. Hull Thickness

3/4"

5/8"

Features: Removable 30 Mesh Stainless Steel Wire

Retail Pkg.

0509DP4CHR

0509DP5CHR

Screen Flame Arrestor (for use with

**OEM Bulk Pkg.** 

0509004CHR

0509005CHR

gasoline applications)



<u> </u>	PR(	DP	65
	WA	RN	ING
(1	Conta	ins L	.ead)

#### **Tank Vent**

Hose

**Size** 5/8"

3/4"

Material: Bronze
Finish: Chrome Plated
For Pipe Size: 3/8" or 1/2" Threads

Features: Removable 30 Mesh Stainless Steel Wire

Screen Flame Arrestor (for use with

gasoline applications)



Fig. (	0503
--------	------

PROP 65 WARNING
(Contains Lead)

Pipe Size	Max. Hull Thickness	Retail Pkg.	OEM Bulk Pkg.
3/8"	7/8"	0503DP3ČHR	0503003CHR
1/2"	7/8"	0503DP4CHR	0503004CHR

### **Tank Vent**

Material: Bronze
Finish: Chrome Plated
For Pipe Size: 3/8" or 1/2" Threads

Features: Removable 30 Mesh Stainless Steel Wire

Screen Flame Arrestor (for use with

gasoline applications)





 Pipe Size
 Max. Hull Thickness
 Retail Pkg.
 OEM Bulk Pkg.

 3/8"
 5/8"
 0515DP3CHR
 0515003CHR

 1/2"
 5/8"
 0515DP4CHR
 0515004CHR

Note: All of the Above Vents are Designed to Meet the Requirements of U.S.C.G. Safety Standards January 31, 1977, for Gasoline Fuel Systems 33 CFR 183.