

Combination Masthead/White All-Round Navigation Lights

2-mile (USCG 2nm) Certified

Use on Power Driven Vessels Under 12m (39.4 ft.) in Length

Material: Polymer Top and Base, Clear Polymer Lens and 3/4" Anodized Aluminum Tube
 Finish: Black
 Contacts: Gold Plated
 Screw Size: #8
 Voltage: 12V (Two Bulbs Included)
 Wattage: 5 watts (each compartment)
 Amperage: .35 amps (each compartment)

Features: Reduced Glare™ Design™
 Two light compartments (Masthead/Anchor)

Fig. 1236: **Fixed Mount** - two pole length sizes

Fig. 1283: **Fixed Mount** - one pole length size

Fold-Down Mts: Feature adjustable angle (0° to 180°) for poles less than 18" long, include adapters available for flat or "V" type 45° mounts and a notch for through base wiring.

Fig. 1281: **Horizontal Mount** - Folds down 90° in either direction opposite the plane of attachment plate of the mount.

Fig. 1284: **Vertical Mount** - Folds down 90° in either direction along the plane of attachment plate of the mount.

0240 Head Style



2
Navigation Lights

Fixed & Folding Mount Options



**Fig. 1281
Horizontal
Mount**



**Fig. 1284
Vertical
Mount**



**Figs. 1236 &
1283
Fixed Mount**

**Fig. 1284
Vertical Mt.
(Shown)**

Base Mount	Height Overall	Base Dimensions	Retail Pkg.	OEM Bulk Pkg.
Fixed Mt.	5"	1" x 2-5/8"	1236DP1BLK	1236001BLK
Fixed Mt.	11-3/8"	1" x 2-5/8"	1236DP2BLK	1236002BLK
Fixed Mt.	3"	1" x 2-5/8"	1283DP0BLK	1283000BLK
Folding				
Horiz. Mt.	13-1/4"	2" x 1-1/2"	1281DP0CHR	1281000CHR
Vert. Mt.	13-1/8"	2-1/4" x 5/8"	1284DP0CHR	1284000CHR



Spare Parts Information

Bulbs (2 per card): 0338DP1CLR.
 Lens Assembly: 0240DP0LNS.

Fig. 0338



Replacement bases for Figs. 1636 & 1639 see page 41



Fig. 0240