

Cat. No. 1612 & 1614 Series Bi-Color Lights

The above lights are designed for use on sail or power driven vessels under 12 meters (39.4 ft.) in length operating on a nominal 12 volt or 24 volt system. In order to comply with the '72 COLREGS and the U.S. Inland Rules, the following must be adhered to:

MOUNTING INFORMATION

Read all instructions before proceeding.

- 1). For proper light selection, positioning and configuration, refer to A.B.Y.C. Standard A-16*, the '72 COLREGS*, and the U.S. Inland Rules**. These lights are usually supplied complete with a 12 volt bulb (Cat. No. 0071DPOCLR - 12V, 10W), however, 24 volt bulbs (Cat. No. 0072DP1CLR) are available for 24 volt systems.

Note: PERKO Series 1612 & 1614 lights used with a 24V Bulb (Cat. No. 0072DP1CLR) are not certified in accordance with 33 CFR 183.810 as these lights are intended for replacement use only on appropriate vessels constructed prior to 11/1/03. All previous certifications apply.

- 2). This light is designed to be mounted on a horizontal surface. (IMPORTANT: top of light must be vertical during operation.)
- 3). Setup for Operation:
Fig. 1612, Insert pole in base, making sure alignment screw in pole slides into notch in base. Push pole down until it engages the electrical connector and then lock by rotating the locking collar clockwise.
Fig. 1614, As pole engages with base, make sure alignment screw in pole slides into the notch in the base. Push the pole until it engages the electrical connector. Turn the threaded collar clockwise until it threads into place and is snug onto the base.

*The above referenced standards can be obtained from:

- | | |
|--|--|
| (1) American Boat & Yacht Council, Inc.
613 Third Street, Suite 10
Annapolis, MD 21403 | (2) U.S. Coast Guard
Washington D.C. 20593
(or your local C.G. Office) |
|--|--|

DIAGRAM #1

NOTE: Top of light must be vertical during operation.



Figs. 1612 & 1614