

Swivel Tank Vent Valves for EPA Compliant Fuel Systems Perko Series 0588S0A for Aluminum Tanks

INSTALLATION INSTRUCTIONS PLEASE READ ALL INSTRUCTIONS BEFORE PROCEEDING

These valves are for use on fuel tanks to comply with the CARB and EPA standards and meet the requirements of U.S.C.G. Safety Standards (July 31, 2011) for 40 CFR Parts 9, 60, 80 et al. (Control of Diurnal Emissions From Nonroad Spark-Ignition Engines and Equipment). **Note: Inspect valve fitting and snap ring annually for corrosion, replace if necessary.**

Series 0588S0A Tank Vent Valves (TVV)

1. This valve is designed to mount on an aluminum surface.
2. Select your mounting location. Drill 1-3/4" diameter hole for valve receiver.
3. Weld the receiver to the tank
4. Slide the valve into receiver and orient hose barb in the direction of the vent line. Attach locking snap ring to hold valve in the receiver.
5. Attach 5/16" vent hose onto hose barb and tighten using hose clamps in accordance with ABYC Fuel System Vent Hose Clamping Standards (H24 Table 3).



*The above referenced standards can be obtained from:

- | | | |
|---|---|--|
| (1). American Boat & Yacht Council, Inc.
613 Third Street, Suite 10
Annapolis, MD 21403 | (2) U.S. Coast Guard
Washington, D.C. 20593
(or your local C.G. office) | (3). E.P.A.
401 "M" Street S.W.
Washington, D.C. 20460 |
|---|---|--|