DERKO "NEW PRODUCT BULLETUN





High Performance LED Floodlight



Fig. 1643 Series 50



Black LED Spotlight



Benefits & Features:

- **7,500 Lumens** (Approx. at 12VDC)
- Voltage: 12VDC, 24VDC, 32VDC auto detect
- 5000K neutral white optics
- Beam Angle: 80° (Flood)

20° (Spot)

 Current Draw: 3.8A at 12VDC

1.9A at 24VDC

- Total power consumption: 50 watts at 12VDC
- Marine grade aluminum mounting bracket included
- Dimensions: 7.0" x 5.5" x 1.9" (with bracket)
- Weight: 2.3 lbs.
- · Available Black or White
- Designed and assembled in USA
- 5 Year Limited Warranty
- 10 Year limited Warranty/Light Engine assembly

High Performance Specifications

• Water Resistance: IP68 Certified

• Temperature Range: -40°C to 55°C Vibration Resistance: MIL-STD-202G

Ordering Information			
Color	Туре	Catalog Number	
White White Black Black	Flood Spot Flood Spot	1643050F0W 1643050S0W 1643050F0B 1643050S0B	



PERKO* NEW PRODUCT BULLETIN





High Performance LED Floodlight



White LED Floodlight

Fig. 1643 Series 100



Black LED Spotlight



Benefits & Features:

- **13,300 Lumens** (Approx. at 12VDC)
- **16,670 Lumens** (Approx. at 24VDC)
- Voltage: 12VDC, 24VDC, 32VDC auto detect
- 5000K neutral white optics
- Beam Angle: 76° (Flood)

25° (Spot)

Current Draw: 8.8A at 12VDC

5.7A at 24VDC

- Total power consumption: 110 watts at 12VDC
- Marine grade aluminum mounting bracket included
- Dimensions: 12.9" x 9.5" x 3.1" (with bracket)
- Weight: 11 lbs.
- Available Black or White
- Designed and assembled in USA
- 5 Year Limited Warranty
- 10 Year limited Warranty/Light Engine assembly

High Performance Specifications

· Water Resistance: **IP68** Certified Temperature Range: -40°C to 55°C

Vibration Resistance: 100,000 cycles, 3-axes

ANSI C136.31

Ord	Ordering Information				
Color	Туре	Catalog Number			
White	Flood	1643100F0W			
White	Spot	1643100S0W			
Black	Flood	1643100F0B			
Black	Spot	1643100S0B			



PERKO* NEW PRODUCT BULLETIN





High Performance LED Spotlight



White LED Spotlight



Benefits & Features:

- **40,000 Lumens** (Approx. at 12VDC)
- 50,000 Lumens (Approx. at 24VDC)
- Voltage: 12VDC, 24VDC, 32VDC auto detect
- 5000K neutral white optics
- Beam Angle: 25° (Spot)

76° (Flood)

26A at 12VDC **Current Draw:**

18A at 24VDC

- Total power consumption: 304 watts at 12VDC
- Marine grade aluminum mounting bracket included
- Dimensions: 14.6" x 20.7" x 3.6" (with bracket)
- Weight: 32 lbs.
- Available Black or White
- Designed and assembled in USA
- 5 Year Limited Warranty
- 10 Year limited Warranty/Light Engine assembly

High Performance Specifications

Water Resistance: **IP68** Certified Temperature Range: -40°C to 55°C

Vibration Resistance: 100,000 cycles, 3-axes

ANSI C136.31

Ordering Information				
Color	Туре	Catalog Number		
White	Flood	1643300F0W		
White	Spot	1643300S0W		
Black	Flood	1643300F0B		
Black	Spot	1643300S0B		



PERKO* NEW PRODUCT BULLETIN





Remote Electric Mount High Performance LED Spotlight





Benefits & Features:

- **40,000 Lumens** (Approx. at 12VDC)
- **50,000 Lumens** (Approx. at 24VDC)
- Voltage: 12VDC, 24VDC, 32VDC auto detect
- 5000K neutral white optics
- 76° (Flood) Beam Angle:

25° (Spot)

Current Draw: 26A at 12VDC

18A at 24VDC

- Total power consumption: 304 watts at 12VDC
- Marine grade aluminum mounting bracket included
- Dimensions: 14.6" x 20.7" x 3.6" (LED Housing)
- Weight: 32 lbs. (LED Housing)
- Available Black or White
- Designed and assembled in USA
- 5 Year Limited Warranty
- 10 Year limited Warranty/Light Engine assembly

High Performance Specifications

 Water Resistance: **IP68** Certified Temperature Range: -40°C to 55°C

· Vibration Resistance: 100,000 cycles, 3-axes

ANSI C136.31

Or	Ordering Information				
Color	Туре	Catalog Number			
White White Black Black	Flood Spot Flood Spot	16443D0F0W 16443D0S0W 16443D0F0B 16443D0S0B			

Note: Retrofit Kit also available to upgrade any existing PERKO Fig. 0887 light assembly